

SPECIFICATION

TITLE OF THE INVENTION

DISC DRIVING APPARATUS

BACKGROUND OF THE INVENTION

5 The present invention relates to a disc driving apparatus
equipped with an optical pickup for reproducing or
reproducing/recording of information on an optical disc, and in
particular, it relates to the disc driving apparatus, being
suitable for so-called a CD-ROM drive, a DVD-ROM drive, and a DVD-RAM
10 drive, etc.

As a laser light generation device and an optical disc
read-out/write-in apparatus equipped with it, according to
conventional art, as was described in, for example, Japanese Patent
Laying-Open No. Hei 10-283650 (1998) (conventional art 1), there
is known such a device, in which a thermal conductive sheet is
disposed between a first heat radiation member and a second heat
radiation member, wherein a contacting area is increased between
the first heat radiation member and the second heat radiation member,
comparing to the case where the both members are contacted with
15 directly, thereby radiating heat, being generated in a
semiconductor laser element as a heat-generating element, into
the second heat radiation member effectively, so as to cool down
the semiconductor laser element with high efficiency.

Also, as an optical pickup, according to the conventional
25 art, as was described in, for example, Japanese Patent Laying-Open
No. Hei 6-111357 (1994) (conventional art 2), there is also known
such an optical pickup with using a prism made of plastic therein,

for providing an optical pickup that can detect an excellent signal without shifting of an optical axis within the plastic prism due to change of temperature, wherein a spacer for use of heat insulation is put between an optical system constructing the optical pickup and a silicon substrate, on which a laser diode, as the heat generating element, is provided for emitting a laser light into the optical system, so as to form a layer of an air having low thermal conductivity, thereby enabling radiation of heat conducting from the laser diode into the silicon substrate.

However, in those conventional arts 1 and 2, there is no disclosure about deterioration on the lifetime of parts or elements, erroneous operation, or decrease in reproducing/recording accuracy, accompanying with non-uniform local temperature distribution, due to thermal interference between the adjacent disposition of the heat generating element and/or heat generation of the heat-generating element, therefore, there is a possibility that, in a case where plural numbers of heat-generating elements are disposed neighboring with each other, due to the thermal interference between the heat-generating elements, elements having small heat generation amount and/or ones of low heat-resistance or endurance are affected with the thermal influences by other heat-generating elements, thereby causing the deterioration on the lifetime of elements, the erroneous operation, and/or the decrease in reproducing/recording accuracy.

Namely, in general, within a disc drive or apparatus equipped with the optical pickup, there are mounted a laser diode generating heat when it conducts recording/reproduction operation, a laser driver circuit board, a high frequency module, and plural numbers of parts or elements, such as, a driver coil for use in an objective lens driver, etc., to be connected thermally, in a pickup housing made of metal, and heat generation of those heat-generating elements causes the local non-uniform temperature distribution within the pickup housing, thereby causing the thermal interference between those heat-generating elements. In particular,

accompanying with multi-functions of the disc drive apparatus, various disc drive apparatuses are developed being equipped with CD-R/RW function for recoding information on the disc, DVD-R/RW function for a disc of much larger recording capacity, and/or DVD-RAM function, etc. In those disc drive apparatuses, the detection light (i.e., a laser light beam) emitted from the laser diode provided within the optical pickup comes to be a very large in the output thereof, and also a large number of heat-generating elements must be disposed neighboring with each other closely, due to a demand of small-sizing thereof. Because of those heat-generating elements, the following problems are caused within the optical pickup:

(1) Thermal interference due to the neighboring disposition of the heat-generating elements;

(2) Thermal deformation due to the locally non-uniform temperature distribution;

(3) The deterioration on the lifetime of elements due to the heat; and

(4) The local rise-up of temperature within an inside of the apparatus due to heat radiation from the elements functioning as heat source, and erroneous operation or malfunction in a circuit system.

SUMMARY OF THE INVENTION

An object, according to the present invention, is to provide a disc driving apparatus, wherein the thermal interference is reduced between the heat-generating elements disposed neighboring with each other, in particular, in the optical pickup, so as to achieve the protection of the heat-generating element from deterioration on the lifetime thereof, thereby having high reliability.

Another object, according to the present invention, is to provide a disc driving apparatus, wherein the thermal interference is reduced between the heat-generating elements disposed neighboring with each other, in particular, in the optical pickup, so as to enable protection of the heat-generating elements from deterioration on the lifetime thereof, and a shift of the detection light is made small, as well, so as to improved the accuracy in reproducing or reproducing/recording, thereby having high reliability and also being able to achieve reproducing or reproducing/recording of information with high definition.

A further other object, according to the present invention, is to provide a disc driving apparatus, wherein the thermal interference is reduced between the heat-generating elements disposed neighboring with each other, in particular, in the optical pickup, so as to enable protection of the heat-generating element from deterioration on the lifetime thereof, and strength or rigidity of a pickup housing is secured, as well, so as to improved the accuracy in reproducing or reproducing/recording, thereby having high reliability and also being able to achieve reproducing or reproducing/recording of information with high definition.

First, according to the present invention, for accomplishing the above-mentioned object, there is provided a disc driving apparatus, comprising: a housing of a disc drive; a rotation mechanism being received within said housing and for rotating a disc; an optical pickup mechanism being received within said housing and for reproducing or reproducing/recording of information on the disc, wherein: said optical pickup mechanism has an optical pickup and a driving mechanism for driving said optical pickup in radial direction of said disc; said optical pickup comprises a pickup housing made of metal, in which are mounted a laser diode emitting a detection light for reproducing or recording the information on said disc, a laser driver circuit board for controlling said laser diode, an objective lens driver for guiding the detection light emitted from a predetermined

position on said disc and for guiding reflection light from said disc onto an optical detector, optical parts, including a lens, a prism, a mirror therein, and an optical detector for detecting said detection light; and said pickup housing mounts said laser diode and said laser driver circuit board with connecting them thermally, to be disposed in adjacent with each other, while providing a thermal separation portion for thermally separating between said laser diode and said laser driver circuit board.

Second, according to the present invention, for accomplishing the above-mentioned object, there is also provided a disc driving apparatus, comprising: a housing of a disc drive; a rotation mechanism being received within said housing and for rotating a disc; an optical pickup mechanism being received within said housing and for reproducing or reproducing/recording of information on the disc, wherein: said optical pickup mechanism has an optical pickup and a driving mechanism for driving said optical pickup in radial direction of said disc; said optical pickup comprises a pickup housing made of metal, in which are mounted a laser diode for emitting a detection light for the use of a CD system, so as to reproduce or record the information on said disc, a laser diode for emitting a detection light for the use of DVD system, so as to reproduce or record the information on said disc, a laser driver circuit board for controlling said laser diode for the use of the CD system, an objective lens driver for guiding the detection light emitted from to a predetermined position on said disc and for guiding reflection light from said disc onto an optical detector, optical parts, including a lens, a prism, a mirror therein, and an optical detector for detecting said detection light; and said pickup housing mounts said laser diode for the use of CD, said laser diode for the use of DVD, said laser driver circuit board and said objective lens driver, with connecting them thermally, wherein said laser diode for the use of CD and said laser driver circuit board are disposed in adjacent with each other, while providing a thermal separation portion for thermally separating between a side of said laser diodes for the

use of CD and DVD and a side of said laser driver circuit board and said objective lens driver.

Third, according to the present invention, for accomplishing the above-mentioned object, there is further provided a disc driving apparatus, comprising: a housing of a disc drive; a rotation mechanism being received within said housing and for rotating a disc; an optical pickup mechanism being received within said housing and for reproducing or reproducing/recording of information on the disc, wherein: said optical pickup mechanism has an optical pickup and a driving mechanism for driving said optical pickup in radial direction of said disc; said optical pickup comprises a pickup housing made of metal, in which are mounted a laser diode for emitting a detection light for the use of CD, so as to reproduce or record the information on said disc, a laser diode for emitting a detection light for the use of DVD, so as to reproduce or record the information on said disc, a laser driver circuit board for controlling said laser diode for the use of CD, an objective lens driver for guiding the detection light emitted to a predetermined position on said disc and for guiding reflection light from said disc onto an optical detector, optical parts, including a lens, a prism, a mirror therein, and an optical detector for detecting said detection light; and said pickup housing is defined by a sidewall formed all around thereof and a bottom wall, and said laser diodes for the use of CD and DVD, said laser driver circuit board and said objective lens driver are mounted therein, with thermally connecting thereamong, wherein said laser diode for the use of CD and said laser driver circuit board are disposed in adjacent with each other, while providing a thermal separation portion for thermally separating between a side of said laser diodes for the use of CD and DVD and a side of said laser driver circuit board and said objective lens driver.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an exploded perspective view of a disc driving

apparatus, according to a first embodiment of the present invention;

Figs. 2(a) and 2(b) show a plane view and a cross-section view of an optical pickup in the disc driving apparatus mentioned above;

Figs. 3(a) and 3(b) show a plane view and a cross-section view of an optical pickup in the disc driving apparatus, according to a second embodiment of the present invention; and

Figs. 4(a) to 4(d) are views for explaining the condition of thermal flow-through in the disc driving apparatus mentioned above.

DESCRIPTION OF PREFERRED EMBODIMENTS

Hereinafter, embodiments according to the present invention will be fully explained by referring to the attached drawings. However, same reference numerals indicate the same elements or equivalents thereof in each of embodiments.

First, explanation will be given on a first embodiment according to the present invention, by referring to Figs. 1 to 3.

First of all, the total structure of the disc driving apparatus according to the present embodiment and the operation thereof will be explained by referring to Fig. 1. This Fig. 1 is an exploded perspective view of the disc driving apparatus according to the first embodiment of the present invention.

A disc driving apparatus 40, being a DVD-ROM apparatus corresponding the CD-R/RW, comprises a disc driver housing 41 as the structure thereof, a disc loading mechanism for carrying a disc 1 into an inside of the disc driver housing 41 or out from

the disc driver housing 41, and a reproducing/recording mechanism for reproducing/recording information on the disc 1. This disc driving apparatus 40 is installed, for example, within a computer apparatus, to be used therein. Further, the present invention is applicable to within a certain extend of the structure, being common or corresponding to, such as a CD-ROM drive, a DVD-RAM driver, etc.

The disc driver housing 41 comprises: sidewalls 42 in a rectangular shape on a plane view thereof, a mechanical base 7 formed within this sidewalls 42, a top cover for covering over an upper surface opening of the sidewalls 42, and a bottom cover 9 for covering a lower surface opening of the sidewalls 42, whereby defining an inner space being almost closed with them, so as to store elements accompanying heat-generation therein. Furthermore, since the disc driver housing 41 is thinned in the thickness thereof, upon the demand of small-sizing of the apparatus, to be small in the inner space, therefore accompanying with the large capacity of the heat-generating elements, the thermal condition require for the elements stored comes to be sever or strict. And, in a front panel 10 constructing a front surface of the sidewalls 42 is formed a transportation or access opening 10a for carrying out/in a disc tray 11 therethrough.

The disc loading mechanism comprises: the disc tray 11 including a mounting portion 11a for mounting the disc thereon, a transportation or access driver mechanism for carrying the disc tray 11 into the disc driver housing 41 through the access opening 10a, so as to mount a spindle motor 2 on it, a disc clamper 3 for fixing the disc 1, being mounted with the spindle motor thereon, to a turntable of the spindle motor 2, and an up-down driver mechanism for moving a unit mechanical chassis 5, so as to fix the spindle motor 2 by means of a disc clamper 3. The access driver mechanism and the up-down driver mechanism is made up with a loading motor, a gear for transmitting driving force of a motor, and a driving force transmitting member, etc. Also, the disc clamper 3 is attached

on the top cover 8 at a predetermined position thereof.

The reproducing/recording mechanism comprises: a rotation driver mechanism for rotating the disc 1, an optical pickup mechanism for performing reproducing/recording of information on the rotating disc 1, in more details thereof, it comprises the unit mechanical chassis 5, a unit holder, the spindle motor 2 mounted on the unit mechanical chassis 5, the optical pickup 4 mounted on the mechanical chassis 5, and a disc clasper 3 attached on the top cover 8. Further, the disc 1 is an information recording medium in a disc-like shape thereof.

The unit mechanical chassis 5 is formed in about a rectangular shape on the top plane view thereof, and is attached on the unit holder not shown in the figure at every corner thereof through elastic members 6a-6d. Further, the unit holder is inserted into the mechanical base 7 to be connected therewith. The elastic members 6a-6d are provided for the purpose of attenuation of vibration and/or shock transmitted from an outside of the apparatus to the unit mechanical chassis 5. And, the spindle motor 2 has a turn table for mounting the disc 1 thereon, and rotates the disc 1 at high revolution speed while holding it, together with the disc clasper 3, for the purpose of the reproducing/recording thereof. The disc clasper 3 is attached on the top cover 8 at the position just above the spindle motor 2.

Also, the optical pickup mechanism comprises the optical pickup 4 for reproducing information on the disc 1 which is mounted on the spindle motor and for recording information thereon, and a radial direction driver mechanism for shifting or moving that optical pickup 4 into the radial direction of the disc 1.

Herein, explanation will be given on the total operation of such the disc driving apparatus 40. The operation of the disc driving apparatus 40 is made up with a disc loading operation of transporting the disc 1 into the disc drive housing 41, so as to

bring the disc 1 into a reproducible or recordable condition thereof, and a reproducing/recording operation for performing the reproducing/recording of the disc 1 which is loaded into.

The disc loading operation will be explained. First, the access driver mechanism of the disc loading mechanism is actuated, thereby to make the disc tray 11 projecting out from the access opening 10a (in the condition shown in the Fig. 1), and after the disc 1 is mounted on the mounting portion 11a, the access driver mechanism is actuated, again, to carry the disc tray 11 into an inside of the disc drive housing 41, thereby mounting it on the turn table of the spindle motor 2. Next, for fixing it by means of the disc clamper 3 which is provided on the surface of the top cover 8, opposing to the disc 1, the spindle motor 2, the optical pickup 4, and the unit mechanical chassis 5 holding those thereon are elevated by means of the up-down driver mechanism, as one unit.

Explaining the reproducing/recording operation, under the condition that the disc 1 is loaded into the disc drive housing 41 to be fixed with the spindle motor 2, the spindle motor 2 rotates at the predetermined revolution speed, thereby to rotate the disc 1. Under this condition, the reproducing and recording of information on the information on the disc by shifting or moving the optical pickup 4 provided on the unit mechanical chassis 5 in the radial direction of the disc 1.

Next, explanation will be given on the details of the optical pickup 4 mentioned above, by referring to Figs. 2(a) and 2(b). The Figs. 2(a) and 2(b) show a plane view of the optical pickup in the disc driving apparatus shown in the Fig. 1 and the cross-section view thereof. Further, the Fig. 2(a) is the plane view, while the Fig. 2(b) the A-A cross-section view in the Fig. 2(a).

The optical pickup 4 comprises a pickup housing 24 for mounting each element of the parts, which are necessary for the

reproducing/recording. This pickup housing 24 of a box type is made of metal material having good thermal conductivity, such as aluminum, magnesium, zinc, etc., and is made up with sidewalls 24a and a bottom wall 24b, to be formed in about a trapezoidal shape in the plane view thereof. On the sidewall 24a at one side (i.e., in the upper side in the Figs. 2(a) and 2(b)) is formed an opening 24c, through which a guide bar 21 penetrates, and two (2) slide bearings 22 are inserted with pressure into both end portions within this opening 24c. Also, on the sidewall 24a at the other side (i.e., in the lower side in the Figs. 2(a) and 2(b)) is formed a bearing 23 therewith as an unit while projecting therefrom. And, the guide bar 21 extending in both sides for axially supporting the bearing 22, and the guide bar 21 extending in both sides for axially supporting the bearing 23 are provided on both side of the pickup housing 24. With this, the pickup housing 24 is movable in the radial direction of the disc 1 (in the horizontal direction in the Figs. 2(a) and 2(b)), thereby being supported freely slidable with a guiding axis of the guide bar 21.

Within an inside of the pickup housing 24 are provided parts or elements, such as, two (2) detector systems for the use of both CD and DVD, respectively. Namely, the pickup housing 24 comprises: a laser diode 27 (of wavelength: 780 nm) for the use of CD, a laser diode 28 (of wavelength: 650 nm) for the use of DVD, both as the detection light source, a prism 31 for guiding those detection lights upon the disc 1, a mirror 30, a collimator lens 32, a common photo-detector 34, for the use both of CD and DVD, for detecting the reflection light from the disc 1, a driver circuit board 29 for the laser diode 27 for the use of CD (hereinafter, only "for CD"), a driver circuit for the laser diode 28 for the use of DVD (hereinafter, only "for DVD"), a high frequency module, and a front monitor 35, etc., as well as, an objective lens driver 26, which is equipped with an objective lens for determining the detection light on the disc 1 at a predetermined position accurately, etc.

For the purpose of dispositions of those parts or elements,

the pickup housing 24 is formed in the box-like shape, wherein the laser diode 27 for CD, the laser diode 28 for DVD, the photo-detector 34 and so on are attached at cut-out portion (or an opening-like portion) provided on a sidewall 24a of the pickup housing 24, while other optical parts or elements are mounted on a bottom wall 24b within an inside of the pickup housing 24, and further the laser driver circuit board 29 on a lower surface of the bottom wall 24b.

Among the parts or elements mentioned above, being installed within the optical pickup 4, the followings accompany with heat generation thereof when the apparatus perform the reproducing/recording operation; the driver coil, which is used in the objective lens driver 26, the laser diode 27 for CD, the laser diode 28 for DVD, the laser driver circuit board 29, the high frequency module, etc., and those are mounted on the pickup housing 24 while being connected therewith thermally. With this, each of those heat-generating elements radiates the heat through transporting it into the pickup housing 24, when it generates the heat and rises up temperature thereof. Also, those heat-generating elements are disposed to be adjacent with each other in vicinity thereof, in the tendency of recent remands for small-sizing of the optical pickup 4. In particular, the laser diode 27 for CD and the laser driver circuit board 29 are disposed very close to each other. In addition, the laser diode 27 for CD increases up an output thereof remarkably, in particular when performing the recording operation, comparing to that when performing the reproducing, thereby increasing the heat generation with this, however, in general, it has a low heat-resistance temperature.

And, within the pickup housing 24 is provided a thermal separation portion at the position between the laser diode 27 for CD and the laser driver circuit board 29, for the purpose of thermally separating them. This thermal separation portion is extended, so that a side of the laser driver circuit board 29 and the objective lens driver 26 is separated from a side of the laser diode 27 for

CD and the laser diode 28 for DVD, thermally, and this is constructed with a slit portion and a recessed gutter formed in the pickup housing 24 and a heat separation member 25.

The heat separation member 25 is made of material, being smaller in thermal conductivity thereof than that of the pickup housing 24, such as a PPC resin (polyphenylene sulfide), polycarbonate, polystyrene, etc., and it is so provided, that it separates the laser diode 27 for CD, thermally, from the pickup housing 24, which is positioned between the laser diode 27 for CD and the laser driver circuit board 29. In case of taking the strength or rigidity of the pickup housing 24 into the consideration, it is preferable to put in or mix a material of, such as glass filler, etc., into the material thereof, for rising up the rigidity thereof. This heat separation member 25 is filled up within an inside of the slit, which divides the bottom wall 24b into two (2), and within the recessed gutter on the lower surface side of the sidewall 24a on an extended line from this slit portion, so as to be formed as one unit. The recessed gutter of this sidewall 24a is located in the middle between the laser diode 27 for CD and the laser driver circuit board 29. In this manner, the heat separation member 25 is provided within the pickup housing 24, for the purpose of heat separation between the laser diode 27 for CD, which emits a large amount of heat generation when recording information on the disc corresponding to the CD-R/RW, and the laser driver circuit board 29 for the use of CD within the housing. In other words, the heat separation portion 25 is provided, so that the pickup housing 24 is divided into two (2), thermally, between the laser diode 27 for CD and the laser driver circuit board 29 for the use of CD.

Also, the heat separation member 25 is provided almost all over the entire width in both directions of the pickup housing 24, so as to separate the laser driver circuit board 29 and the objective lens driver 26 from the laser diode 27 for CD and the laser diode 28 for DVD, thermally. And, the prism 31, the mirror

30 and the optical detector 34 are positioned in the same side to the laser diode 27 for CD and the laser diode 28 for DVD.

As was mentioned in the above, the pickup housing 24 is made of such the metal material, aluminum, magnesium, zinc, etc., and the thermal conductivity is about 200 kcal/mh°C for aluminum, about 150 kcal/mh°C for magnesium, about 100 kcal/mh°C for zinc, therefore the heat generated from the heat-generating elements 26 to 29 is preferably conducted to the pickup housing 24, to be radiated from the surface of the pickup housing 24. In this case, the thermal conductivity of the heat separation member 25 is about 0.2 kcal/mh°C since it is made of the resin material. With this, putting the heat separation member 25 between them enables to make as about 0.001 times small as the thermal flow-through within the pickup housing 24. And, as apparent from the Fig. 2, with the structure of providing the heat separation member 25 on the bottom surface side within the pickup housing 24 and being covered on the side surface thereof with a member of the pickup housing 24, the housing and the heat separation member can be formed as one unit.

Further, it is also possible to make the space of the slit portion and the recessed gutter formed in the pickup housing 24 in a form of an air layer, but not filling up the space with the heat separation material 25. In this case, the thermal conductivity of the air is about 0.03 kcal/mh°C, being smaller than that of the material of resin group, therefore it has a large effect on the heat separation, but the rigidity of the optical pickup 4 is lowered, then the heat separation member 25 will be needed to be provided if the rigidity is necessary for the optical pickup 4. Also, if the slit portion and the recessed gutter in the pickup housing 24 are formed in a fin-like structure (i.e., a concave and convex structure), in the case of being filled up with the air therein to form the air layer, it is possible to improve an effect of heat radiation into an air, remarkably, with the effect of heat separation.

With such the structure of the optical pickup 4 mentioned above, the heat generated from the laser diode 27 for CD use is radiated upon the lower side of the pickup housing 24, in the Figs. 2(a) and 2(b), and that from the laser driver circuit board 29 is radiated upon the upper side of the housing, in the Figs. 2(a) and 2(b), therefore it is possible to achieve an effective heat radiation, so that a uniform thermal distribution can be brought about over the pickup housing 24. In this case, on the lower side of the pickup housing 24 being separated by the heat separation member 25, there are disposed the laser diode 28 for DVD use, and so on, which also generates the heat when the apparatus operates, and also on the upper side of the housing the objective lens driver 26, etc. However, since they do not have such the large amount of heat generation as the laser diode for CD use, and also since the distance between those elements is larger than that between the laser diode 27 for CD use and the laser driver circuit board 29, as well as, in the heat radiation volume by means of the pickup housing 24, therefore the thermal interference is smaller than that between the laser diode 27 for CD and the laser diode driver circuit board 29 for the CD use.

In the present embodiment, a portion lies in the pickup housing 24 being formed as one unit, where the laser diode 27 for CD and the laser diode 28 for DVD, the prism 31, the mirror 30, the lens 33, the optical detector 34, etc., are disposed, and it is not divided into sections by means of the heat separation member 25, then the thermal deformation of the pickup housing 24 is small, therefore it is possible to make the relative positional shift and/or angular shift (a tilt of the element) between those elements small, thereby to improve the accuracy in the reproducing/recording operation.

According to the present embodiment, it is possible to prevent the thermal interference from occurring between the elements provided within the optical pickup 4, therefore it enables the effective use of the pickup housing 24 as the heat radiation member,

thereby protecting the laser diodes 27 and 28 from deterioration on the lifetime due to the heat. With this, it is possible to obtain a disc driving apparatus being highly reliable and able to achieve the high definition reproducing/recording.

5 Next, explanation will be given on a second embodiment according to the present invention, by referring to Figs. 3 and 4. The Figs. 3(a) and 3 (b) show a plane view and a cross-section view of an optical pickup in the disc driving apparatus according to the second embodiment, and in particular, the Fig. 3(a) the
10 plane view and the Fig. 3(b) the B-B cross-section view in the Fig. 3(a). The Fig. 4 is a view for explaining about the condition of flow-through within the optical pickup mentioned above. However, in this second embodiment, explanation will be omitted on a portion duplicating with those in the first embodiment. Also, in this second
15 embodiment, the constituent elements commonly provided in the first embodiment achieve the same effects thereof.

 The function of the optical pickup 4 is to reproduce or record information on the disc 1. For this reason, in the disc driving apparatus 40 (see the Fig. 1), there is provided a means for shifting or moving the optical pickup 4 to a predetermined position on the disc 1, and as a guide for it, in the side of the apparatus, for example, there is provided a main shaft guide bar 21 (the upper side in the Figs. 3(a) and 3(b)) and a secondary shaft guide bar (the lower side in the Figs. 3(a) and 3(b)). For supporting the
25 pickup housing 24 to be freely slidable in the direction of the guide bar 21, two (2) pieces of slide bearings 22 (for the main shaft) are inserted with pressure onto the pickup housing 24, on the side of the main shaft guide bar 21, and on the side of the secondary shaft guide bar 21 is formed only one (1) piece of the
30 slide bearing 23 with the housing as one unit.

 Within an inside of the pickup housing 24, there are provided two (2) detection systems for the CD and the DVD, i.e., the parts or elements, such as, the laser diode 27 (of wavelength, 780 nm)

for the CD use and the laser diode 28 (of wavelength, 650 nm) for the DVD use as the detection light source, the mirror 30, the prism 31 and the collimator lens 32 for guiding those detection light upon the disc 1, the optical detector 34 commonly for use in the CD and DVD, for detecting the reflection light from the disc 1, the driver circuit board 29 for the laser diode 27 for CD, and the driver circuit and the high frequency module for the laser diode 28 for CD, and the objective lens driver 26 equipped with the objective lens for determining the detection light on the disc 1 at the predetermined position accurately, etc. A mirror 30 is attached on an each upper surface of the laser diodes 27 and 28 for CD and DVD, so that the detection light emitted from each of the laser diodes 27 and 28 is polarized into an inner direction on the surface of the optical pickup 4. For positioning those parts or elements therein, the pickup housing 24 is formed into the box-like shape with the sidewall 24a and the bottom wall 24b, wherein the laser diode 27 for CD, the laser diode 28 for DVD, the optical detector 34, etc., are mounted on the bottom surface of the housing being attached from the bottom surface side thereof, while the other optical parts or elements are mounted within an inside of the housing.

With the present embodiment, the heat separation member 25 is provided in the pickup housing 24 for separating the laser diode 27 for CD, the laser diode 28 for DVD, the laser driver circuit board 29 and the objective lens driver 26 from the others, thermally within the inside of the housing, among those mounted elements accompanying heat generation therein when the apparatus operates. The pickup housing 24 is made of the metal material, such as aluminum, magnesium, zinc, etc. The heat separation member 25 is formed by using the PPC resin (polyphenylene sulfide), polycarbonate, polystyrene, etc. In case of taking the strength or rigidity of the pickup housing 24 into the consideration, it is preferable to put in or mix a material of, such as glass filler, etc., into the material thereof, for rising up the rigidity thereof. The thermal conductivity is about 200 kcal/mh°C for aluminum, about 150

kcal/mh°C for magnesium, about 100 kcal/mh°C for zinc, and 0.2 kcal/mh°C for the material of resin group. Therefore, putting the heat separation members 25 enables to make as about 0.001 times small as the thermal flow-through within the pickup housing 24.

5 Further, it is also possible to separate them by making each of the heat separation members only in the form of a slit, thereby thermally separating them by an air layer. In this case, the thermal conductivity of the air is about 0.03 kcal/mh°C, being smaller than that of the material of resin group, therefore it has a large effect on the heat separation. However, since the rigidity of the optical pickup 4 is lowered, then the heat separation member 25 will be needed to be provided if the rigidity is necessary for the optical pickup 4. Also, if the slit portion and the recessed gutter in the pickup housing 24 are formed in a fin-like structure (i.e., a concave and convex structure), in the case of being filled up with the air therein to form the air layer, it is possible to improve an effect of heat radiation into an air, remarkably, with the effect of heat separation.

10 Also, as shown in the Fig. 3(b), the heat separation members 25 are provided from the bottom surface side of the pickup housing 24, while the side surface thereof is covered with the member of the housing, therefore it is possible to form the pickup housing 24 and the heat separation member 25 together, as one unit rigidly. Further, from the consideration of separation from the heat source portion, such the structure may be applicable, that the heat generating-element is attached on the pickup portion as other element, and thereafter that portion is attached through the heat separation members 25.

15 In a CD hologram unit forming the laser diode 27 for CD and a light detector 34 for the CD system together as an unit, or in a DVD hologram unit forming the laser diode 28 for DVD and a light detector 34 for the DVD system together as an unit, the provision

of the heat separation member 25 between those elements enables protection thereof from the thermal interference between them, and further since no shifting of the detection light occurs on the optical detector 34 as far as no deformation is caused in the hologram unit portion, even when the housing portion is deformed due to a partial deformation by the heat separation member 25, therefore it is possible to realize the optical pickup 4 having high reliability.

In the present embodiment, further, because of the structure of the box-like shape, wherein the laser diode 27 for CD, the laser diode 28 for DVD and the optical detector 34 are provided on the bottom wall of the pickup housing 24, thereby surrounding the optical pickup 4 by the side walls in every direction thereof, therefore it is possible to improve the rigidity of the pickup housing 24, remarkably. For example, improvements can be obtained on the rigidity of the pickup housing 24 against bent and/or twist, and on the vibration characteristics due to local deformation, or the like, and also relative positional shifting and/or angular shifting between the optical elements due to the deformation in the static pickup housing 24 can be suppressed.

According to those embodiment, it is possible to protect the elements from the thermal interference between them, thereby protecting those elements from deterioration on the lifetime thereof. With this, it is possible to provide the optical pickup 4 having high reliability. Also, an improvement can be obtained on the reliability with the disc driving apparatus, in which such the optical pickup is applied.

Next, by referring to Figs. 4(a) to 4(d), explanation will be given on the structure, for the heat flow-through (arrows in the figure indicate the heat flows within the optical pickup housing members) and for thermal separation within the pickup housing 24, with the functions and effects thereof. Herein, the explanation is given on the case, assuming that the heat-generating elements

within the optical pickup 4 are the laser diode 27 for CD, the laser diode for DVD, the laser driver circuit board 29 for the CD and the driver coil equipped with the objective lens driver 26, as shown in the figure.

Fig. 4(a) shows the thermal flow-through (the flow of heat within the optical pickup housing members) from the heat-generating elements when operating within the optical pickup 4, but having no thermal separation structure therein. In general, an output of the laser diode 27 or 28 comes to be very large when recording information on the disc 1, comparing to the case of reproducing information on the disc 1. In the case of the DVD-ROM corresponding to the CD-R/RW, the laser diode 28 for DVD is only for the use of reproducing, exclusively, however the laser diode 27 for CD is used for both the recording/reproducing, therefore the heat generation from the laser diode 27 is large, in particular when recording. Also, the laser driver circuit boards 29 provided within the housing is electrically connected with the laser diode 27, and they should be disposed neighboring to each other by taking noises and unnecessary radiation into the consideration. For this reason, the thermal interference occurs due to the mutual heat generation between the laser diode 27 for CD and the laser driver circuit 19 for the CD, and that portion comes to be the condition of being saturated thermally. Thus, it results into the rise-up of temperature of a portion of the laser diode 27, thereby bringing about the deterioration of the lifetime of the laser diode 27 and/or malfunctions on the laser driver circuit board or each of the circuit boards provided with the apparatus. Also, the thermal interference occurs due to heat radiation from the laser diode 28 for DVD and the driver coil equipped within the objective lens driver 26, participating with the other heat-generating elements, and it causes the thermal deformation on the housing through thermal distribution within the pickup housing 24, etc. The thermal deformation of the housing brings about the relative optional shifting and the angular shifting, etc., between the optical elements, thereby causing deterioration on the optical

characteristics (i.e., the shifting of the optical axis, and the positional shifting of an optic point on the optical detector).

Fig. 4(b) shows a principal idea of the present invention, in which each of the heat-generating elements is separated within the inside of the optical pickup 4, and the heat separation members 25 are provided for separating those heat-generating elements, respectively. With those heat separation members 25, being made of the material being smaller in the thermal conductivity than that of the housing, the thermal separation can be obtained. Also, with determining the volume of the housing portion, being defined by enclosing with the heat separation members 25, depending upon the heat generation amount of the heat-generating element, it is possible to bring the pickup housing 24 as a whole into the condition of being almost uniform in the thermal distribution therein. With this, the local heat distribution can be eliminated, so that the housing can be reduced down in temperature as a whole.

Fig. 4(c) shows a variation of the heat separation member 25 provided within the optical pickup 4. The heat separation member 25 is disposed in the present variation, so that the laser diode 27 for CD and the laser driver circuit board 29 for the CD are separated from each other. Also, this heat separation member 25 is further elongated, so as to separate the laser diode 28 for DVD from the objective lens driver 26, in the structure thereof. With such the structure of the present variation, as was mentioned in the above, the heat separation member 25 is provided for separating between the laser diode 27 for CD having the largest heat generation amount and the laser driver circuit board 29 for the CD, thermally, thereby protecting them from the thermal interference therebetween, and the heat flow from the each element is detected in the direction opposite to the heat separation member 25, thereby enabling to use the pickup housing 24 as the heat radiation member, effectively. In this case, the thermal interference between the laser diode 27 for CD and the laser diode 28 for DVD, or between the laser driver circuit board 29 for CD

and the objective lens driver 26 is small, from the positional relationships between the heat generation amount from the respective elements and the distance between them (or, the cross-section area, through which the heat conducts).

Also, the structure of the variation mentioned herein is effective, in particular, in the case where it is applied into an optical system having the CD system or the DVD system, wherein the optical elements, such as, the laser diodes 27 and 28, the optical detector 34, the prism 31 for guiding detection light from the laser diode 27 or 28 onto the objective lens of the objective lens driver 26, so as to be irradiated upon the disc 1 at the predetermined position thereof, and for guiding the reflection light from the disc 1 back to the optical detector 34, the mirror 30, the lens 33, etc., are installed in the form of separate elements, respectively. This is, because the deformation is difficult to be formed, when the thermal deformation is caused in the pickup housing 24 due to the heat radiation from the each heat-source element, or when the vibration characteristic (bent mode, twist mode, local deformation mode) is caused due to the rigidity of the portion of the pickup housing 24, since the portion where the optical elements are installed is formed as one unit (no provision of the heat separation member 25). If the material of the resin group or the like is used for the heat separation member 25, the stress accompanying with the deformation is concentrated on this heat separation member 25, thereby relieving the stress on the portion where the optical elements are attached in advance, therefore it has an effect to suppress the deformation.

Fig. 4(d) shows the C-C cross-section of the optical pickup 4 shown in the Fig. 4(c). As apparent from this figure, the laser diode 27 for CD is provided with a cut-out portion from the bottom surface of the portion of the pickup housing 24, so as to be disposed at the predetermined position, thereby to be attached to. The laser driver circuit board 29 for the CD is attached onto the bottom surface of the pickup housing 24. The heat separation member 25

is provided between those two (2) elements, however according to the present variation, with provision of a groove-like cut-out on the bottom surface of the pickup housing 24, the heat separation member 25, being made of material being smaller in the thermal conductivity than that used for the housing, is inserted into this groove portion. Of course, it may be formed with the pickup housing 24 as one unit. Arrows shown in the figure indicate the heat flows from the heat-generating elements. Since the cross-section area of the housing portion between the elements (i.e., between the laser diode 27 for CD and the laser driver circuit board 29 for the CD use) comes to be small for the heat separation member 25, the heat amount flowing through this cross-section also comes down to be small, thereby enabling the thermal cut-off between the elements. As a result of this, it is possible to protect the elements from the thermal interference therebetween. Herein, the cross-section area is remained a little bit between the elements, but since it is for the forming as one unit, therefore it is also possible to completely cut-off by the heat separation member 25 between them.

In each of those embodiments mentioned above, the heat separation member(s) 25 is/are provided in a straight line-like manner, however the heat separation member(s) 25 may be provided with a curved portion, a deleted portion therein, or may be in such the structure that the cross-section area is changed in a portion thereof.

According to each of those embodiments mentioned above, with the provision of the heat separation member(s) 25 within the optical pickup 4, it is possible to separate the elements, such as, the laser diode 29 and the laser driver circuit board 29, etc., generating heat when reproducing information on the disc 1 or when recording the information on it, thermally within the pickup housing 24, therefore it is possible to protect those elements 27 and 29 from the thermal interference therebetween. With this, each of those heat-generating elements 27 and 29, being disposed

to be adjacent to each other, is able to radiate the heat stably, without having the hear radiation effects from the other elements, therefore it is possible to protect it from the deterioration on the lifetime thereof. Also, with provision of the heat separation
5 member 25 by taking the heat generation amount of the heat-generating elements 26 to 29 and the heat radiation volume in the housing members into the consideration, it is possible to obtain the uniform change in temperature of the pickup housing 24, thereby enabling the protection of the pickup housing 24 from
10 the thermal deformation due to the local temperature distribution thereon. As a result of this, the detection light emitted from the laser diode 27 or 28 is guided onto the disc 1, and it is prevented from the relative positional shift and/or the shift in inclination, etc., within the optical elements, such as, the prism, the mirror,
15 the lens, etc., for guiding the reflection light from the disc 1 onto the optical detector 34. In the disc driving apparatus using such the optical pickup, it is possible to protect the circuits from the malfunction thereof, and also obtain an improvement on the reliability of the apparatus, thereby providing the disc
20 driving apparatus with the high definition.

As was fully explained in the above, according to the present invention, it is possible to reduce the thermal interference between the heat-generating elements disposed to be adjacent to each other in the optical pickup, so as to prevent the
25 heat-generating elements from being deteriorated in the lifetime thereof, thereby obtaining the disc driving apparatus having high reliability.

Also according to the present invention, it is possible to reduce the thermal interference between the heat-generating
30 elements disposed to be adjacent to each other in the optical pickup, so as to prevent the heat-generating elements from being deteriorated in the lifetime thereof, and also to make the shifting of the detection light small, so as to improve the accuracy in the operation of reproducing or reproducing/recording, thereby

obtaining the disc driving apparatus having high reliability and being capable of the high definition reproducing or reproducing/recording.

- Further, according to the present invention, it is possible
- 5 to reduce the thermal interference between the heat-generating elements disposed to be adjacent to each other in the optical pickup, so as to prevent the heat-generating elements from being deteriorated in the lifetime thereof, and also to maintain the strength of the pickup housing, so as to improve the accuracy in
- 10 the operation of reproducing or reproducing/recording, thereby obtaining the disc driving apparatus having high reliability and being capable of the high definition reproducing or reproducing/recording.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209